

VISCOSITY MODIFIERS

HiTEC[®] 5748

Non-Dispersant Olefin Copolymer Viscosity Modifier



Versatility and logistical simplicity across multiple applications

HiTEC® 5748 Non-Dispersant Olefin Copolymer Viscosity Modifier

Versatility and logistical simplicity across multiple applications

Application

HiTEC® 5748 is recommended for use in various Engine Oils, selected Off Road, and Grease applications making it highly versatile:



Licensable PCMO applications from API SL to OEM applications such as MB 229.5



Licensable HDEO applications from API CH-4 to OEM applications such as MB 228.51



JASO compliant for MCO applications from API SG to API SN quality



Fit for use for selected off-road applications



Used in grease applications to provide structural stability and reduce soap content

Typical Characteristics

Appearance:	Clear to slightly hazy greenish tan viscous liquid
Specific Gravity @ 15.6/15.6°C:	0.855
Flash Point, °C (PMCC):	135 min.
Color, ASTM D1500:	3.0 max.
Kinematic Viscosity @ 100°C, cSt:	1100
Dilute Viscosity @ 100°C, cSt:	11.55
Shear Stability Index %:	22

Handling Information

Max Handling Temp: 250°F (120°C)
Shelf Life: 36 months @ 10 – 40 °C

Key Performance Benefits

- Single viscosity modifier for multiple applications
- Logistical simplicity
- Excellent shear stability requirements
- Proven in the field
- Exceeds Bosch stay-in-grade shear stability requirements
- Surpasses Sequence VIII stay-in-grade requirements
- Robust low-temperature properties

Recommended Dosage

Dosages of HiTEC® 5748 generally necessary to make multigrade crankcase oils which meet the 10 hour L-38 stay-in-grade requirements are given below, with CMCC (DIN 51382) stay-in-grade recommendations in parentheses:

SAE Grade	5W-30	10W-30	10W-40	15W-40	20W-50
HiTEC® 5748 (vol.)	8.0%	5.7%	11.6%	5.4%	5.4%
	(8.0%)	(5.8%)	(11.8%)	(5.5%)	(5.5%)

Please contact your Afton Chemical representative for specific recommendations.